














Mitsubishi

**PRINTERS: COLOR PRINTERS**

MODEL	KEY FEATURES
<p>CP-30DW <b>NEW</b></p> 	<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> USB 2.0</li> </ul> <p><a href="#">DETAILS</a></p>
<p>CP-700DU</p> 	<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> Centronics parallel and MS Windows 95/98 driver (Macintosh driver/adaptor and Windows NT 4.0 drivers optional) (For SCSI interface: model CP700DSU)</li> </ul> <p><a href="#">DETAILS</a></p>
<p>CP-770DW</p> 	<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> Parallel/SCSI (optional)</li> </ul> <p><a href="#">DETAILS</a></p>
<p>CP-800UM</p> 	<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> RGB analog video, NTSC composite video, S-video, RS-232C port, front and rear remote jacks.</li> </ul> <p><a href="#">DETAILS</a></p>
<p>CP-800DW</p> 	<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> SCSI-2, Centronics</li> </ul> <p><a href="#">DETAILS</a></p>
<p>CP-910U</p> 	<ul style="list-style-type: none"> <li><input type="checkbox"/> Sublimation thermal transfer</li> <li><input type="checkbox"/> S-Video/composite video</li> </ul> <p><a href="#">DETAILS</a></p>
<p>CP-900DW</p> 	<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> USB1.1</li> </ul> <p><a href="#">DETAILS</a></p>

CP-900UM		<ul style="list-style-type: none"> <li><input type="checkbox"/> Sublimation thermal transfer method</li> <li><input type="checkbox"/> RGB/S-Video/composite video, RS-232C Control</li> </ul> <p><a href="#">DETAILS</a></p>
CP-980DW		<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> USB1.1</li> </ul> <p><a href="#">DETAILS</a></p>
CP-2000UA		<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> Parallel, RS-232C, RGB analog (15-85 kHz &amp; 45-80 Hz vertical)</li> </ul> <p><a href="#">DETAILS</a></p>
CP-2000DU		<ul style="list-style-type: none"> <li><input type="checkbox"/> Dye sublimation thermal transfer</li> <li><input type="checkbox"/> SCSI-2, Fast Centronics</li> </ul> <p><a href="#">DETAILS</a></p>

**PRINTERS: MONOCHROME PRINTERS**

MODEL	KEY FEATURES
P-93DW	<div style="display: flex; align-items: center;">  <ul style="list-style-type: none"> <li><input type="checkbox"/> Thermal printing on thermal sensitive paper</li> <li><input type="checkbox"/> USB 2.0</li> </ul> <p><a href="#">DETAILS</a></p> </div>
P-500W	<div style="display: flex; align-items: center;">  <ul style="list-style-type: none"> <li><input type="checkbox"/> Thermal</li> <li><input type="checkbox"/> BNC (input and output) Video-NTSC/PAL</li> </ul> <p><a href="#">DETAILS</a></p> </div>
P-93W	<div style="display: flex; align-items: center;">  <ul style="list-style-type: none"> <li><input type="checkbox"/> Thermal printing on thermal sensitive paper</li> <li><input type="checkbox"/> BNC (input and output)</li> </ul> <p><a href="#">DETAILS</a></p> </div>

**MEDICAL IMAGING: MEDICAL VCRS**

MODEL	KEY FEATURES
-------	--------------

MD3000U



- EIA standard NTSC color signal
- S-VHS/VHS 1/2" width high-density videocassette
- More than 400 lines (S-VHS, VHS-ET mode); more than 240 lines (VHS mode)

 **DETAILS**

MD3000U-  
2S



- EIA standard NTSC color signal
- S-VHS/VHS 1/2" width high-density videocassette
- More than 400 lines (S-VHS, VHS-ET mode); more than 240 lines (VHS mode)

 **DETAILS**

MD3000U-  
2P



- EIA standard NTSC color signal
- S-VHS/VHS 1/2" width high-density videocassette
- More than 400 lines (S-VHS, VHS-ET mode); more than 240 lines (VHS mode)

 **DETAILS**

MD3000U-  
3



- EIA standard NTSC color signal
- S-VHS/VHS 1/2" width high-density videocassette
- More than 400 lines (S-VHS, VHS-ET mode); more than 240 lines (VHS mode)

 **DETAILS**